



Quality counts. As one of the leading factory fill specialists we supply high performance quality. Today and tomorrow. Therefore VOLVO counts on lubricants and specialities of FUCHS.

PRODUCT	CHARACTERISTICS	SPECIFICATIONS/ APPROVALS
Motor Oils		
TITAN CARGO MAXX SAE 5W-30 	Premium MAXX Performance Engine Oil with new XTL®-Technology. Specially developed for vehicles with modern exhaust after treatment and turbocharger. Optimum cold starting properties and ageing stability for extreme fuel-economy over the whole drain-interval.	ACEA E6 VOLVO VDS-3
TITAN CARGO MAXX SAE 10W-40 	Premium MAXX Performance Engine Oil with new XTL®-Technology. Specially developed for vehicles with modern exhaust after treatment and turbocharger. Good cold starting properties and ageing stability for fuel-economy over the whole drain-interval.	ACEA E9/E7/E6 API CJ-4 VOITH-RETARDER „B“ VOLVO VDS-3/CNG
TITAN CARGO SL SAE 5W-30	Ultra High Performance, extreme fuel-economy engine oil for a variety of commercial vehicle diesel engines, with optimum cold starting and lower oil consumption. Specially developed for extended service intervals.	ACEA E7/E4 VOLVO VDS-3
TITAN CARGO MC SAE 10W-40	Ultra High Performance, fuel-economy engine oil based on MC-synthesis for a variety of commercial vehicle diesel engines. Specially developed for extended service intervals. Good cold starting and lower oil consumption.	ACEA E7/E4 API CI-4 VOLVO VDS-3
TITAN CARGO SAE 5W-40	Ultra High Performance, fuel-economy engine oil, specially developed for commercial vehicle diesel engines with extended service intervals, exhaust after treatment and turbocharger.	ACEA E9/E7 API CJ-4 VOLVO VDS-4
TITAN CARGO EU6 SAE 5W-30	Ultra High Performance, fuel-economy engine oil for use in many OEM Euro 6 engines fitted with modern exhaust after treatment devices. Excellent cold starting properties and low oil consumption.	ACEA E9/E7/E6 API CJ-4 VOLVO VDS-4
TITAN CARGO SAE 10W-30	Ultra High Performance, fuel-economy engine oil, specially developed for commercial vehicle diesel engines with extended service intervals, exhaust after treatment and turbocharger.	ACEA E9 API CJ-4 VOLVO VDS-4
TITAN CARGO SAE 15W-40	Ultra High Performance, fuel-economy engine oil for a variety of commercial vehicle diesel engines. Specially developed for Volvo with extended service intervals, exhaust after treatment and turbocharger.	ACEA E9 API CJ-4/CI-4 PLUS/CI-4 VOLVO VDS-4

PRODUCT	CHARACTERISTICS	SPECIFICATIONS/ APPROVALS	FUCHS RECOM- MENDATIONS
Automatic Transmission Fluids (ATF)			
TITAN ATF 5005	Premium Performance ATF for automatic transmission in motor vehicles. Outstanding base oil quality for optimal cold temperature properties and high ageing stability. Durable friction properties for excellent wet clutch performance. Product dyeing: red.	VOITH H55.6336.xx ZF TE-ML 04D, 14B, 16L, 17C	VOLVO 97341 ZF TE-ML 02F, 11B, 14C
TITAN ATF 4000	Ultra High Performance ATF for use in automatic transmissions as well as other ATF applications. Licensed according to DEXRON III (H). Improved low-temperature shifting compared to DEXRON II. Product dyeing: red.	VOITH H55.6335.xx VOLVO 97341 ZF TE-ML 04D, 14A	ZF TE-ML 02F, 03D, 09, 11B, 17C

PRODUCT	CHARACTERISTICS	SPECIFICATIONS/ APPROVALS	FUCHS RECOM- MENDATIONS
Gear Oils			
TITAN CYTRAC SL SAE 75W-90	Premium Performance Gear Oil for highly-stressed hypoid axles in commercial vehicles formulated with fully-synthetic base oils. Developed for the longest oil change intervals in commercial vehicle axle drives.	API GL-5	VOLVO 97312 ZF TE-ML 05B, 07, 08, 12B, 16F, 17B
TITAN CYTRAC ULTRA SYNTH SAE 75W-80	Premium Performance Gear Oil for extended drain intervals in commercial vehicles, especially developed for ZF heavy duty transmissions with and without Intarder. Reduces fuel consumption by improving gearbox efficiency. Suitable for longest oil change intervals.	API GL-4 VOLVO 97307 ZF TE-ML 01E, 02E, 16P	
TITAN CYTRAC MAN SYNTH SAE 75W-80	Premium Performance Gear Oil for extended drain intervals in commercial vehicles manual gearboxes, specially developed for manual and automatic ZF-gearboxes, formulated with fully-synthetic base oils. Reduces fuel consumption by improving gearbox efficiency. Suitable for the longest oil change intervals and compatible with Carbon-Synchronizers.	API GL-4 ZF TE-ML 01L, 02L, 16K	VOLVO 97307
TITAN CYTRAC LD SAE 75W-80	Ultra High Performance Gear Oil for extended oil change intervals in commercial vehicles fitted with integral intarders or supplementary retarders.	API GL-4	VOLVO 97305 ZF TE-ML 02D, 08
Antifreeze			
MAINTAIN FRICOFIN LL	Premium Performance Coolant Additive based on monoethylene glycol. Free from nitrite, amine, phosphate and silicates. Product dyeing: orange.	ASTM D 3306 TYPE I BS 6580	VOLVO 128 6083/002 (=VOLVO TRUCKS, VOLVO CE, from MY 2005)
MAINTAIN FRICOFIN	Super High Performance Coolant Additive based on monoethylene glycol. Free from nitrite, amine and phosphate. Product dyeing: blue-green.	AFNOR NF R 15-601 TYPE 1 ASTM D 3306 TYPE I ASTM D 4985 BS 6580:1992 VOITH TURBO 172.00225010	
Fuel Additives			
MAINTAIN Diesel Effect	Super High Performance Fuel Additive improving Diesel fuel properties for singular as well as constant treatment.		
MAINTAIN Winterfit	Super High Performance Diesel Fuel and Heating Oil Additive to prevent waxing and plugging at low temperatures.		
Greases			
RENOLIT LZR 000	Semi-fluid grease for engine vehicle central lubrication systems. Gear grease for gearboxes in municipal machinery. Observe manufacturer's recommendations, -40 °C to +110 °C.		
RENOLIT LX-PEP 2	Special grease based on lithium complex soaps for long-life applications. Good corrosion protection, thermally and mechanically stable, specially suitable for wheel bearings of cars and trucks, -30 °C to +150 °C.		
PLANTOGEL ECO 2 S	Environmentally compatible, rapidly biodegradable EP-grease based on lithium soap and synthetic esters for the lubrication of plain and roller bearings. Good pumpability in central lubrication systems, awarded with the EU-Ecolabel, temperature range -40 °C up to +120 °C.		

The information contained in this product information leaflet is based on the experience, knowledge and expertise of FUCHS SCHMIERSTOFFE GMBH in the development and manufacturing of lubricants and represents the current state of the art. The performance of our products can be influenced by a series of factors, especially the specific use, the method of application, the operational environment, component pretreatment, possible external contamination, etc. For this reason, universally valid statements about the function of our products are not possible. The information given in this product information represents general, non-binding guidelines. No warranty expressed or implied is given concerning the properties of the product or its suitability for any given application. We therefore recommend that you consult a FUCHS SCHMIERSTOFFE GMBH application engineer to discuss application conditions and the performance criteria of the products before the product is used. It is the responsibility of the user to test the functional suitability of the product and to use it with the corresponding care. Our products are subject to continuous further development. We therefore retain the right to change our product program, the products, and their manufacturing processes as well as all details of our product information sheets at any time and without warning. With publication of this product information leaflet, all previous editions cease to be valid. Any form of reproduction requires express prior written permission from FUCHS SCHMIERSTOFFE GMBH.
© FUCHS SCHMIERSTOFFE GMBH. All rights reserved. Version 12/2015

FUCHS SCHMIERSTOFFE GMBH Export Division

Friesenheimer Straße 19 · 68169 Mannheim / Germany
Phone: +49 621 3701-1703 · Fax: +49 621 3701-7719
export@fuchs-schmierstoffe.de · www.fuchs-schmierstoffe.de

LUBRICANTS.
TECHNOLOGY.
PEOPLE.

