



# LUBRICANTS FOR VOLVO PASSENGER CARS



Quality counts. As one of the leading factory fill specialists we supply high performance quality. Today and tomorrow. Therefore VOLVO counts on lubricants and specialities of FUCHS.

Product	Description	Specifications	Approvals	FUCHS Recommendations
<b>Engine Oils</b>				
<b>TITAN</b> <b>GT1 PRO V</b> <b>SAE 0W-20</b>  	Premium Performance Engine Oil with new XTL®-Technology in ground-breaking viscosity class. Specially designed for modern VOLVO vehicles, for extreme fuel-economy characteristics and reduced CO <sub>2</sub> emissions. Excellent cold starting behaviour, very fast oil circulation and outstanding performance reserves.	ACEA A1/B1	VOLVO VCC RBS0-2AE	–
<b>TITAN</b> <b>Supersyn FE</b> <b>SAE 0W-30</b>	Ultra High Performance, fuel-economy engine oil for a variety of vehicles with or without extended service intervals. Excellent cold starting properties and low oil consumption.	ACEA A5/B5	VOLVO VCC 95200377	–
<b>TITAN</b> <b>Supersyn LONGLIFE</b> <b>SAE 0W-30</b>	Ultra High Performance, extreme fuel-economy engine oil for a variety of vehicles with or without extended service intervals. Excellent cold starting and lower oil consumption.	ACEA A3/B4	–	–
<b>TITAN</b> <b>Supersyn LONGLIFE</b> <b>SAE 5W-40</b>	Ultra High Performance, fuel-economy engine oil for a variety of vehicles with or without extended service intervals. Optimum cold starting and lower oil consumption.	ACEA A3/B4	–	–
<b>Gear Oils</b>				
<b>TITAN</b> <b>SINTOFLUID FE</b> <b>SAE 75W</b>	Premium Performance Manual Transmission Fluid offering increased gearbox efficiency in passenger cars due to low viscosity level. Reduces fuel consumption and offers best properties at low temperature. Suitable as fill for life fluid according to manufacturer.	API GL-4	–	–
<b>TITAN</b> <b>SINTOFLUID</b> <b>SAE 75W-80</b>	Premium Performance Manual Transmission Fluid for passenger cars. Offering good gearbox efficiency. Suitable as fill for life fluid according to manufacturer.	API GL-5	–	VOLVO 97308
<b>TITAN</b> <b>SINTOPOID FE</b> <b>SAE 75W-85</b>  	Premium Performance fuel-economy passenger car axle fluid offering increased gearbox efficiency in passenger cars due to low viscosity level. Reduces fuel consumption and offers best properties at low temperature. Suitable as fill for life fluid according to manufacturer.	API GL-5	–	–
<b>TITAN</b> <b>SINTOPOID LS</b> <b>SAE 75W-90</b>	Premium Performance, fully-synthetic multifunctional gear oil, formulated with fully-synthetic base oils. Suitable for axles and transfer gear-boxes with or without self-locking differentials and also as trouble shooter for conventional manual transmissions.	API GL-4/-5/-5 incl. LS	–	–
<b>Automatic Transmission Fluids (ATF)</b>				
<b>TITAN</b> <b>ATF 4000</b>	Ultra High Performance ATF for use in automatic transmissions as well as other ATF applications. Licensed according to DEXRON III (H). Improved low-temperature shifting compared to DEXRON II. Product dyeing: red.	–	DEXRON III (H)	–
<b>TITAN</b> <b>ATF 4400</b>	Ultra High Performance ATF specifically formulated for Japanese passenger cars and light commercial vehicles, as well as for several European and American manufacturers. The high torque capacity exceeds the performance of many original fluids. Product dyeing: red.	–	–	DEXRON III AISIN WARNER/AW-1 JWS 3309/TYP E T-IV

Product	Description	Specifications	Approvals	FUCHS Recommendations
<b>Central Hydraulic / Power Steering Fluids</b>				
<b>PENTOSIN</b> <b>PENTOSIN CHF 11S</b>	Premium Performance Power Steering and Central Hydraulic Fluid with a wide application and approval profile for various manufacturers. Product dyeing: green.	–	–	VOLVO 1161529
<b>PENTOSIN</b> <b>PENTOSIN CHF 20Z</b>	Premium Performance Power Steering and Central Hydraulic Fluid with a wide application and approval profile for various manufacturers. Product dyeing: green.	–	–	VOLVO 30741424
<b>Antifreeze</b>				
<b>MAINTAIN</b> <b>FRICOFIN</b>	Super High Performance Coolant Additive based on monoethylene glycol. Free from nitrite, amine and phosphate. Product dyeing: blue-green.	AFNOR NF R 15-601 TYPE 1 AS/NZS 2108:2004 TYPE A ASTM D 3306 TYPE I ASTM D 4985 BS 6580:2010 CUNA NC 956-16 SAE J814 SAE J1034	–	–
<b>MAINTAIN</b> <b>FRICOFIN HDD</b>	Ultra High Performance Engine Coolant concentrate based on monoethylene glycol. Free of amines and phosphates with low silicate technology. Product dyeing: yellow.	ASTM D 3306 TYPE I ASTM D 4985 ASTM D 6210 TYPE I-FF ASTM D 7583 AS/NZS 2108:2004 TYPE A BS 6580:2010 SAE J814	–	–
<b>Brake Fluids</b>				
<b>MAINTAIN</b> <b>MAINTAIN DOT 4</b>	Super High Performance Brake Fluid for hydraulic brake systems and clutch actuation in passenger cars, trucks and motorcycles.	FMVSS NR. 116 DOT 3/ DOT 4 ISO 4925 CLASS 3/4 SAE J1703/J1704	–	–
<b>MAINTAIN</b> <b>MAINTAIN DOT 5.1</b>	Ultra High Performance Brake Fluid for hydraulic brake systems and clutch actuation in passenger cars, trucks and motorcycles.	FMVSS NR. 116 DOT 5.1 ISO 4925 CLASS 3/4/5.1 SAE J 1703/J 1704	–	–

The information contained in this product information is based on the experience and know-how of FUCHS SCHMIERSTOFFE GMBH in the development and manufacturing of lubricants and represents the current state-of-the-art. The performance of our products can be influenced by a series of factors, especially the specific use, the method of application, the operational environment, component pre-treatment, possible external contamination, etc. For this reason, universally-valid statements about the function of our products are not possible. Our products must not be used in aircrafts/spacecrafts or their components, unless such products are removed before the components are assembled into the aircraft/spacecraft. The information given in this product information represents general, non-binding guidelines. No warranty expressed or implied is given concerning the properties of the product or its suitability for any given application. We therefore recommend that you consult a FUCHS SCHMIERSTOFFE GMBH application engineer to discuss application conditions and the performance criteria of the products before the product is used. It is the responsibility of the user to test the functional suitability of the product and to use it with the corresponding care. Our products undergo continuous improvement. We therefore retain the right to change our product program, the products, and their manufacturing processes as well as all details of our product information sheets at any time and without warning, unless otherwise provided in customer-specific agreements. With the publication of this product information, all previous editions cease to be valid. Any form of reproduction requires express prior written permission from FUCHS SCHMIERSTOFFE GMBH.

© FUCHS SCHMIERSTOFFE GMBH. All rights reserved. Edition 09/2017

## FUCHS SCHMIERSTOFFE GMBH

Export Division ▪ Friesenheimer Straße 19 ▪ 68169 Mannheim/Germany

Phone: 0621 3701-1703 ▪ Fax: 0621 3701-7719

E-mail: [export@fuchs-schmierstoffe.de](mailto:export@fuchs-schmierstoffe.de) ▪ [www.fuchs.com/de/en](http://www.fuchs.com/de/en)