



LUBRICANTS.  
TECHNOLOGY.  
PEOPLE.



LUBRICANTS FOR  
**VW-GROUP\***  
PASSENGER CARS



Quality counts. As one of the leading factory fill specialists we supply high performance quality. Today and tomorrow. Therefore VW-GROUP\* counts on lubricants and specialities of FUCHS.

2014 FUCHS received the Volkswagen Group Award.

PRODUCT	CHARACTERISTICS	SPECIFICATIONS/ APPROVALS
<b>Motor Oils</b>		
<b>TITAN GT1 PRO C-3</b> SAE 5W-30 	Premium Performance, extreme fuel-economy engine oil with new XTL®-Technology for optimum cold start ability and outstanding performance reserves. For modern passenger cars and light commercial vehicles with or without extended service intervals. Specially developed for BMW, VW and Mercedes-Benz vehicles with exhaust after treatment and turbocharger.	ACEA C3 VW 504 00/507 00
<b>TITAN GT1 PRO FLEX</b> SAE 5W-30 	Premium Performance, extreme fuel-economy engine oil with new XTL®-Technology for optimum cold start ability and outstanding performance reserves. For modern passenger cars and light commercial vehicles with or without extended service intervals. Specially developed for BMW, Mercedes-Benz and Opel vehicles with exhaust after treatment and turbocharger.	ACEA C3 API SN/SM VW 502 00/505 00/505 01
<b>TITAN GT1</b> SAE 5W-40 	Premium Performance, fuel-economy engine oil with new XTL-Technology for optimum cold start ability and outstanding performance reserves. For modern passenger cars and light commercial vehicles with or without extended service intervals. Specially developed for vehicles with exhaust after treatment and turbocharger.	ACEA C3 API SN/SM/CF VW 502 00/505 00/505 01
<b>TITAN Supersyn LONGLIFE PLUS</b> SAE 0W-30	Ultra High Performance, extreme fuel-economy engine oil formulated with fully synthetic base oil for VW engines. Specially developed for VW Longlife Technology. For all passenger car gasoline and diesel engines with or without pump injector technology. Excellent cold starting and lower oil consumption.	VW 503 00/506 00/506 01
<b>TITAN Supersyn LONGLIFE</b> SAE 5W-40	Ultra High Performance, fuel-economy engine oil for a variety of vehicles with or without extended service intervals. Optimum cold starting and lower oil consumption.	ACEA A3/B4 API SN/SM/CF VW 502 00/505 00

PRODUCT	CHARACTERISTICS	SPECIFICATIONS/ FUCHS RECOMMEN- DATIONS
<b>Gear Oils</b>		
<b>TITAN SINTOFLUID FE</b> SAE 75W	Premium Performance Manual Transmission Fluid offering increased gearbox efficiency in passenger cars due to low viscosity level. Reduces fuel consumption and offers best properties at low temperature. Suitable as fill for life fluid according to manufacturer.	API GL-4 VW TL 521 71 (G 052 171 A1/A2) VW TL 521 78 (G 052 178 A2) VW TL 525 12 (G 052 512 A2) VW TL 726 (G 052 726 A2/G 055 726 A2/ G 060 726 A2/G 070 726 A2)
<b>TITAN SINTOFLUID</b> SAE 75W-80	Premium Performance Manual Transmission Fluid for passenger cars. Offering good gearbox efficiency. Suitable as fill for life fluid according to manufacturer.	API GL-5 VW 501 50 (G 005 000 05/G 005 000/G 005 000 20/G 052 911 A1/A2)
<b>TITAN SINTOPOID FE</b> SAE 75W-85	Premium Performance Gear Oil offering increased gearbox efficiency in passenger cars due to low viscosity level, formulated with fully-synthetic base oils. Reduces fuel consumption and offers best properties at low temperature. Suitable as fill for life fluid according to manufacturer.	API GL-5 VW TL 521 45-X (G 052 145 A1) VW TL 521 90 (G 052 190 A2/ G 055 190 A2)
<b>TITAN SINTOPOID</b> SAE 75W-90	Premium Performance Axle Gear Oil for passenger cars, also for high-off-set hypoid drives offering good gearbox efficiency. Suitable as fill for life fluid according to manufacturer.	API GL-5 VW TL 521 45-Y (G 052 145 A2)

\* VW is a registered trademark of VW AG, Wolfsburg

PRODUCT	CHARACTERISTICS	APPROVALS
---------	-----------------	-----------

### Double Clutch Transmission Fluids (DCTF)

<b>TITAN</b> DCTF 52529	Premium Performance DCTF, specially developed for the Audi DL382 Double Clutch Transmission with wet clutch. Provides optimum wear protection and excellent friction properties even under hard conditions and offers best shifting performance over the whole lifetime.	VW TL 52 529-C
-------------------------	--	----------------

PRODUCT	CHARACTERISTICS	FUCHS RECOM-MENDATIONS
---------	-----------------	------------------------

### Double Clutch Transmission Fluids (DCTF)

<b>TITAN</b> DCTF	Premium Performance DCTF, specially developed for modern Double Clutch Transmission with wet clutch. The wide performance profile offers the use in diverse Double Clutch Transmissions of different manufacturers. Provide optimum wear protection and excellent shifting properties even under hard conditions over the whole lifetime.	VW (AUDI, SEAT, SKODA) 6-speed FWD
-------------------	---	------------------------------------

### Automatic Transmission Fluids (ATF)

<b>TITAN</b> ATF 5005	Premium Performance ATF for automatic transmission in motor vehicles. Outstanding base oil quality for optimal cold temperature properties and high ageing stability. Durable friction properties for excellent wet clutch performance.	DEXRON III (H) VW TL 521 62 (G 052 162) ZF TE-ML 02F, 11B, 14C
<b>TITAN</b> ATF 4400	Ultra High Performance ATF specifically formulated for Japanese passenger cars and light commercial vehicles. The high torque capacity exceeds the performance of many original fluids.	DEXRON III VW G 052 990/055 025
<b>TITAN</b> ATF CVT	Ultra High Performance ATF specially designed for use in many CVT-gearboxes using push-belts or transmission chains made of steel.	VW TL 521 80 (G 052 180) VW TL 525 16 (G 052 516)

### Central Hydraulic / Power Steering Fluids

<b>TITAN</b> ZH 4300 B	Premium Performance Central Hydraulic Oil formulated with fully-synthetic base oils.	VW TL 521 46 (G 002 000)
<b>TITAN</b> ZH 3044	Ultra High Performance power steering and central Hydraulic Oil for automotive applications.	VW G 004 000

### Antifreeze

<b>MAINTAIN</b> FRICOFIN LL	Premium Performance Coolant Additive based on monoethylene glycol. Free from nitrite, amine, phosphate and silicates. Product dyeing: orange.	VW TL 774 D/F (different colour)
<b>MAINTAIN</b> FRICOFIN V	Ultra High Performance Coolant Additive based on monoethylene glycol. Free of nitrites, amines and phosphates. Product dyeing: pink - violet.	VW TL 774 J (G13)
<b>MAINTAIN</b> FRICOFIN DP	Ultra High Performance Coolant Additive based on monoethylene glycol. Free from nitrite, amine and phosphate. Product dyeing: pink - violet.	VW TL 774-G

PRODUCT	CHARACTERISTICS	APPROVALS
---------	-----------------	-----------

### Greases

<b>RENOCAL</b> FN 745/94	Low temperature optimized grease for lubrication of door locks, seat mechanisms, window lifters and pedals.	VW TL 745
<b>RENOLIT</b> MP 735	Multi-purpose grease used for lubrication of wheel bearings.	VW TL 735
<b>RENOLIT</b> MP 735 X/AZ	Special grease for the general lubrication of spline shafts of constant velocity joints to avoid fretting corrosion. AZ: Specially for VW T5.	VW TL 735 X/Y
<b>RENOLIT</b> LX-PG 2	Synthetic grease used as mounting aid for brake cylinder boots.	VW TL 521 50

The information contained in this product information leaflet is based on the experience, knowledge and expertise of FUCHS SCHMIERSTOFFE GMBH in the development and manufacturing of lubricants and represents the current state of the art. The performance of our products can be influenced by a series of factors, especially the specific use, the method of application, the operational environment, component pretreatment, possible external contamination, etc. For this reason, universally valid statements about the function of our products are not possible. The information given in this product information represents general, non-binding guidelines. No warranty expressed or implied is given concerning the properties of the product or its suitability for any given application. We therefore recommend that you consult a FUCHS SCHMIERSTOFFE GMBH application engineer to discuss application conditions and the performance criteria of the products before the product is used. It is the responsibility of the user to test the functional suitability of the product and to use it with the corresponding care. Our products are subject to continuous further development. We therefore retain the right to change our product program, the products, and their manufacturing processes as well as all details of our product information sheets at any time and without warning. With publication of this product information leaflet, all previous editions cease to be valid. Any form of reproduction requires express prior written permission from FUCHS SCHMIERSTOFFE GMBH.  
© FUCHS SCHMIERSTOFFE GMBH. All rights reserved. Version 03/2015

## FUCHS SCHMIERSTOFFE GMBH

### Export Division

Friesenheimer Straße 19 · 68169 Mannheim / Germany  
Phone: +49 621 3701-1703 · Fax: +49 621 3701-7719  
export@fuchs-schmierstoffe.de · www.fuchs-schmierstoffe.de

LUBRICANTS.  
TECHNOLOGY.  
PEOPLE.

